

(University of Choice)

MASINDE MULIRO UNIVERSITY OF SCIENCE AND TECHNOLOGY (MMUST)

MAIN CAMPUS

UNIVERSITY SPECIAL/SUPPLEMENTARY EXAMINATIONS 2018/2019 ACADEMIC YEAR

FIFTH YEAR FIRST SEMESTER EXAMINATIONS

FOR THE DEGREE

IN

BACHELOR OF SCIENCE IN CIVIL AND STRUCTURAL ENGINEERING

COURSE CODE: CSE 531

COURSE TITLE: SEWERAGE AND WASTEWATER

TREATMENT

DATE: TUESDAY 28TH MAY 2019 TIME: 2.00PM - 4.00PM

INSTRUCTIONS:

- 1. This paper contains **FIVE** Questions
- 2. Answer ALL Questions in Section A and any TWO Questions in Section B
- 3. Marks for each question are indicated in the parenthesis.
- 4. It is in the best interest of the student to write legibly
- 5. Examination duration is **2 Hours**

MMUST observes ZERO tolerance to examination cheating This Paper Consists of 3 Printed Pages. Please Turn Over.

SECTION A – Compulsory (40 Marks)

Question One

- a) Briefly explain the concepts of self-cleaning velocity and non-scouring velocity in sewer design giving their desired values [4 marks]
- b) Calculate the quantity of sewage for a combined sewer system for a town, given the following data:

Area of the town -250 hectares

Intensity of rainfall – 50 mm/hr

Population density – 300 persons/hectare

Rate of water supply – 250 litres/capita/day

Peak factor - 2.0

Surface classification

Type of surface	% Area	Run off coefficient
Roofs	50	0.90
Paved surfaces	30	0.85
Non paved surfaces	20	0.30

Assume 80% of the water supplied reaches the sewer

[6 marks]

- c) A main sewer was designed for an area of 50 km². Density of population of the town is 200 persons/hectare. The average sewage flow is 250 litre/capita/day. The peak discharge is one and half times more than average flow. Rainfall equivalent of 8mm in 24 hours, all of which are runoff.
- i) What should be the capacity of the sewer?

[5 marks]

ii) Find the diameter of the sewer when running full. Take n=0.012 and slope of 1 in 625

[5 marks]

Question Two

a) Describe the significance of screening and grit removal in wastewater treatment

[4 marks]

- b) Design a rectangular grit chamber for a town having a population of 100,000. Assume per capita sewage production as 120 litres/day, horizontal velocity of 30 cm/s, detention time of 60 seconds and settling velocity of 2.2 cm/s. Assume depth is twice its breadth. Take peak factor as 3 [7 marks]
- c) Explain the treatment mechanism in the following waste stabilization ponds

i) Facultative pond

ii) Maturation pond

[5 marks] [4 marks]

SECTION B (Attempt any Two Questions)

Question Three

- a) Calculate the diameter, depth and weir loading of a primary sedimentation tank, using the following data:
 - Sewage flow 6 Million Litres per day
 - Detention period 2 hrs
 - Overflow rate 1500 L/m²/hr

[6 marks]

b) Explain using a suitable sketch the operation of a septic tank

[5 marks]

c) Explain re-circulation in trickling filters and its relevance

[4 marks]

Ouestion Four

- a) Differentiate between suspended and attached growth processes in wastewater treatment. Give one example in each case [5 marks]
- b) A wastewater effluent of 600 L/s with a BOD = 60 mg/l, DO = 2.5 mg/l and temperature of 25°C enters a river where the flow is 30 m³/s and BOD = 3 mg/l, DO = 8.5 mg/l and temperature of 16°C. Deoxygenation constant for the waste is 0.10 per day at 20°C. The velocity of water in the river downstream is 0.15 m/s and the depth of flow is 1.5 m. Determine the following after mixing of wastewater with the river water
- i) Combined discharge (ii) BOD (iii) DO (iv) Temperature

[4 marks]

c) Why is wastewater stabilization ponds preferred method of wastewater treatment in most towns in Kenya? What are the challenges of this method? [6 marks]

Question Five

a) Explain the different tests for the inspection of a sewer

[6 marks]

- b) Describe the concept of urine diverting toilet as a sustainable sanitation technology [4 marks]
- c) Outline factors favouring disposal of treated wastewater to water bodies

[5 marks]